



JKL PART NUMBER	LENGTH A +/- 1.5mm	COLOR (REF.)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (Cd/m <sup>2</sup> )	*RATED LIFE (HRS)
BF20218-24B	218mm	RGB HIGH OUTPUT WHITE 8400°k x = .290 y = .305	1250 @ 0°C	500	5 ± 1	46,000 TYP.	20,000 MIN. 40,000 AVG.
BF20226-24B	226mm		1275 @ 0°C	510			
BF20292-24B	292mm		1650 @ 0°C	660			
BF20325-24B	325mm		1830 @ 0°C	735			

\*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 THIRD ANGLE PROJECTION	<b>METRIC</b> DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0	 <b>JKL COMPONENTS CORPORATION</b>			
	TITLE <b>MINIATURE COLD CATHODE          FLUORESCENT LAMP</b>				
DRAWN BY <b>L. WENGSTROM</b>	APP'VD BY DATE <b>J.K. 4/26/04</b>	SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>BF 20-24B</b>	
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE <b>NONE</b>	RELEASED DATE <b>8/14/03</b>	REVISION DATE <b>4/26/04</b>	REV. NO. <b>A</b> SHEET <b>1 OF 1</b>

REV. NO.	DESCRIPTION/ECO NUMBER	APP'VD DATE
<b>A</b>	RATING ADDITIONS & CHANGES RELEASED TO CAD MULTI LIST	4/26/04 8/14/03