



**Notes:**

1. Material and Finish:
  - Receptacle Housing: Polyester (Black), UL94 V-0;
  - (b) or ABS, Nickel Plated, UL94 V-0,
  - Duplex LC Adaptor Assembly:
    - Housing: Mod. PPO, UL94 V-0,
    - Color: **SM Blue/MM Beige/APC SM Green**
    - Alignment Sleeves: SM Ceramic/MM Phosphor Bronze
    - Dust Cap: PP, Color: Neutral transparent
  - Operating Temperature: -40°C to +85°C
2. Connector can be mounted to a maximum panel thickness of 3.2mm.
3. IP67 rated when covered or fully mated with the appropriate mating connector

Directive 2002/95/EC RoHS Compliant

(b)	Description	Plastic Version	Metallized Version
	Single Mode (SM)	17-300790	17-300910
	Multi Mode (MM)	17-300800	17-300920
	APC Single Mode (APC SM)	17-300810	17-300930

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION.	Customer:			Tolerance Unless otherwise specified			Scale:	Dim. in mm	
	Name	Title	Approval Date	0 PLC ±0.50	1 PLC ±0.38		2 PLC ±0.25	3 PLC ±0.10	ANGLES ±3°
				2012	Date	Name	Material: See Notes		
				Draw.	Sept. 28	Vincent Ke	Title: IP67 Industrial Duplex LC Receptacle Assembly Kit		
				Appd.	Sept. 28	J. Chaudry	Plastic Version with bayonet on both sides		
						Norm	Drawing No.: 17K1A332		DIN A3
							Part No.: SEE PART NUMBER TABLE		Sheet 1/1
	Rev.	Changes	Date	Name					