

Model #: S002-18I

SCSI/Fibre Channel - 18-in. Internal SCSI Ribbon Cable 2Conn 50SOK

Highlights

Premium cabling



Description

Tripp Lite's internal 18-in. (1.6ft) 50pin SCSI ribbon cable has 2 connectors and is used to connect internal devices requiring a 50 position interface. This is the internal 50-pin ribbon cable required for narrow and wide SCSI applications (sometimes called SCSI-1 or SCSI-2). Perfect for internal CD-ROM drives and hard drives. Our products are fully tested and certified to meet or exceed applicable industry standards. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

System Requirements

- Narrow SCSI controller
- Internal SCSI device requiring 50 position SCSI interface

Package Includes

• 18 inch internal SCSI ribbon cable 2Conn 50SOK

Features

- 18-in. long
- Two 50SOK(female) narrow SCSI connectors
- Internal 18in 50pin SCSI ribbon cable with 2 connections used to connect internal devices requiring 50position connectors
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest ultra 320 to legacy SCSI-1 and every combination in between
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

OVERVIEW		
Drives Supported	1	
INPUT		
Cable Length (in.)	18	

UPC Codes		
Unit Carton UPC#	037332013736	
CONNECTIONS		
Connector A	50 SOCKET IDC (FEMALE)	
Connector B	50 SOCKET IDC (FEMALE)	
Number of Connectors	2	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=2341.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.