

Article Number: 181-15206



Description: Slotted Cable and Wiring Duct, 1.5" x 2", Non-Adhesive,

PVC, Gray, 30 ft/ctn

Base Data		
	Local Order Number	181-15206
	Туре	SL1.5X2
	Color	Gray (GY)
	Features and Benefits	<ul> <li>Strong fingers prevent unwanted breaking.</li> <li>Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.</li> <li>Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.</li> </ul>
	Quantity Per	box
	Product Description	Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "T's".
	Technical Description	Non-Adhesive
	Short Description	Slotted Cable and Wiring Duct, 1.5" x 2", Non-Adhesive, PVC, Gray, 30 ft/ctn
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	1.5"
	Width W (Metric)	38.1mm
	Width W2 (Imperial)	1.5"
	Width W2 (Metric)	38.1mm
	Width W3 (Imperial)	0.4"
	Width W3 (Metric)	10.2mm
	Width W4 (imperial)	1.0"
	Width W4 (metric)	25.4mm
	Width W5 (imperial)	1.6"
	Width W5 (metric)	40.6mm

generated on: 4/28/2017

## 181-15206



Product Dimensions         Height H (Metric)         52.6mm           Material and Specifications Packaging         Material Polyvinylchloride (PVC)           Material Shortcut         PVC           Flammability         self-extinguishing           Operating Temperature         +122°F (+50°C)           ROHS Compliant         Yes           Certification/Specification         CSA           UL Recognized (US)         Yes           Logistic and Packaging         Package Quantity (Imperial)         30ft           Package Quantity (Metric)         9.14m           Customs Number(Schedule B)         3925900000			
Height H (Metric) 52.5mm  Mounting Hole Centers (Imperial) 4.0"  Material and Specifications  Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification CSA UL Recognized (US) Yes  Logistic and Packaging Package Quantity (Imperial) 30ft Package Quantity (Metric) 9.14m		Height H (Imperial)	2.07"
Material and Specifications  Material  Material  Material  Polyvinylchloride (PVC)  Material Shortcut  PVC  Flammability  Self-extinguishing  Operating Temperature  H122°F (+50°C)  ROHS Compliant  Yes  Certification/Specification  UL Recognized (US)  Yes  Logistic and Packaging  Package Quantity (Imperial)  Package Quantity (Metric)  9.14m		Height H (Metric)	52.6mm
Specifications  Material  Material  Polyvinylchloride (PVC)  Material Shortcut  PVC  Flammability  Self-extinguishing  Operating Temperature  +122°F (+50°C)  ROHS Compliant  Certification/Specification  CSA  UL Recognized (US)  Yes  Logistic and Packaging  Package Quantity (Imperial)  Package Quantity (Metric)  9.14m		Mounting Hole Centers (Imperial)	4.0"
Material Shortcut PVC Flammability self-extinguishing Operating Temperature +122°F (+50°C) ROHS Compliant Yes Certification/Specification CSA UL Recognized (US) Yes  Logistic and Packaging Package Quantity (Imperial) 30ft Package Quantity (Metric) 9.14m			
Flammability  Operating Temperature  +122°F (+50°C)  ROHS Compliant  Yes  Certification/Specification  UL Recognized (US)  Packaging  Package Quantity (Imperial)  Package Quantity (Metric)  9.14m		Material	Polyvinylchloride (PVC)
Operating Temperature +122°F (+50°C)  ROHS Compliant Yes  Certification/Specification CSA  UL Recognized (US) Yes  Logistic and Packaging  Package Quantity (Imperial) 30ft  Package Quantity (Metric) 9.14m		Material Shortcut	PVC
ROHS Compliant  Certification/Specification  CSA  UL Recognized (US)  Packaging  Package Quantity (Imperial)  Package Quantity (Metric)  9.14m		Flammability	self-extinguishing
Certification/Specification UL Recognized (US)  Yes  Logistic and Packaging  Package Quantity (Imperial) Package Quantity (Metric)  9.14m		Operating Temperature	+122°F (+50°C)
Logistic and Packaging  Package Quantity (Imperial) Package Quantity (Metric)  9.14m		ROHS Compliant	Yes
Logistic and Packaging  Package Quantity (Imperial) 30ft Package Quantity (Metric) 9.14m		Certification/Specification	CSA
Packaging  Package Quantity (Imperial) 30ft  Package Quantity (Metric) 9.14m		UL Recognized (US)	Yes
Package Quantity (Metric) 9.14m	Logistic and Packaging		
		Package Quantity (Imperial)	30ft
Customs Number(Schedule B) 3925900000		Package Quantity (Metric)	9.14m
		Customs Number(Schedule B)	3925900000

generated on: 4/28/2017